

CP200 Series

Portable Two-way Radios

CP200

CP200·XLS – Limited Keypad

CP200·XLS – Full Keypad



Motorola— a name you know and trust.

Motorola is a company of firsts with a rich heritage of innovation. We continue to invent what's next—connecting people, delivering mobility and making technology personal. Whether you need a simple yet reliable communication solution or a solution with enhanced functionality to organize multiple work groups, the CP200 Series of two-way radios help keep you and your team working efficiently. Featuring a lightweight, ergonomic design, powerful audio output and operation on both conventional and LTR trunking systems, the CP200 Series portable two-way radios help keep your work force connected. The result—increased productivity for your business.

Exceptional Durability

With superb durability, Motorola's radios are built to last. Motorola's rugged and reliable radios, undergo rigorous testing in the design process. We use U.S. Military Standards and Accelerated Life Testing, so you can be assured Motorola radios will hold up under demanding conditions. These tests are designed to simulate very harsh environments, including:

Rain—Steady rainfall and wind for 30 minutes on every surface.

Salt Fog—48 hours of exposure to an atomized salt solution.

Dust—6 hours of blowing dust on all surfaces.

Vibration—Up to 9 hours of exposure to vibration that simulates the rigors a radio could undergo while being transported.

Shock—18 shocks with a minimum G force of 40 Gs each.

Service Offerings


Even with the quality you have come to expect from Motorola, the every day use of your radios requires on-going maintenance to help ensure your radios are operating at peak performance. Managing the in-house repair and maintenance of your subscriber radios takes a dedicated staff of technicians, as well as an ongoing investment in diagnostic equipment, repair tools, and the technical training to keep up to speed on the latest technology. Motorola has made that investment and can help you easily and cost effectively keep your radios in top operating condition to ensure optimal efficiency and productivity. You can rely on Motorola to support your radio system with these Subscriber Repair service offerings:

• Repair Service Advantage (RSA)

Repair Service Advantage is a post-warranty service offering that extends the service coverage of Motorola subscriber portable or mobile radios. RSA can be purchased as an option to new radio purchases and is available in 1, 2 or 3-year increments. (US only)

• Extended Warranty

In addition to the 2-year standard warranty, Extended Warranty is available for a total of 3 or 5 year coverage. (Canada only)



CP200 portable two-way radio

The design and simple operation of the CP200 portable two-way radio makes it ideal for education, hospitality, retail, manufacturing and security organizations. This radio features a large, textured push-to-talk button, X-Pand™ technology for crisp, clear audio and two programmable buttons for quick access to frequently used features—all in a lightweight, durable design.



Features

CP200 Portable:

- 4/16 Conventional Channels
- **Large Rotary Channel Selector**
Changes channels quickly and easily
- **Rotary On/Off and Volume Control**
- **Tricolor LED**
Indicates radio status and battery levels
- **Accessory Connector**
Convenient access for audio accessories
- **3 Inch Spring Action Belt Clip**
Attaches radio firmly to belt
- **Rugged, Die-Cast Chassis**
With polycarbonate housing for greater protection
- **Large, Textured Push-to-Talk Button**
Easy to find and use, even when wearing gloves
- **Two Programmable Option Buttons**
Supports your choice of up to four product features
- **Privacy Codes Include:**
42 standard TPL codes, 84 standard DPL codes and non-standard codes
- **System Scan and Auto Scan**
- **Single Priority Scan**
Frequently scans higher priority channel
- **Battery Latch Lock**
Secures battery
- **Quik-Call II™ Signaling**
Call Alert
Selective Call
- **MDC 1200 Signaling**
Selective Radio Inhibit
Radio Check
Selective Inhibit
Push-to-Talk ID
- **DTMF Signaling**
DTMF Push-to-Talk ID
- **2-year Standard Warranty**

Programmable Features: Choose up to 4


- Sticky Monitor/Monitor
- Repeater/Talk Around
- Scan
- VOX
- Squelch
- Nuisance Channel Delete
- Power Level

CP200·XLS portable two-way radio

The expanded features of the CP200·XLS portable two-way radio makes it a perfect fit for education, hospitality, retail, manufacturing and security organizations who need additional capabilities and capacity to manage a large workforce. Featuring both conventional and LTR® trunking capability, the CP200·XLS enables you to efficiently organize your workforce. With both a limited keypad and full keypad model, the CP200·XLS also features an 8 character alpha-numeric display, four programmable buttons for quick access to up to eight programmable features and X-Pand™ technology for crisp, clear audio—all in a lightweight, durable design.



Limited and Full Keypad models available.



All CP200-XLS portable models include:

- Li-Ion 2250 mAh Battery
- Rapid Rate Charger
- Antenna – VHF Heliflex or UHF Whip
- 3 Inch Belt Clip
- Quick Reference/Safety and Warranty Guide
- 2-Year Warranty

Features

CP200-XLS Limited and Full Keypad Portables:

- 128 Conventional Channels
- Up to 100 LTR Talkgroups
- Up to 10 Sites and 100 Talkgroups in LTR
- Mixed Assignment of Conventional Personalities and LTR Talkgroups
- Up to 20 Repeaters per Site in LTR
- Up to 4 Universal IDs per System in LTR
- Up to 40 Universal IDs per Radio in LTR
- Up to 8 Programmable Features
- Supports up to 16 Scan Lists of up to 16 Channels Per List – Limited Keypad only
- User-Editable Standard TPL/DPL Codes
- User-Editable Scan List
- Lights On/Off
Keypad and display backlights

- Tones On/Off
- Call Tone Tagging
Tag a special tone for a particular call
- Quik-Call II™ Signaling Includes:
Selective Call Encode: Calls a specific group or individual
Call Alert Encode: Notifies a specific group/individual with an alert tone and lighted LED
- DTMF Signaling Includes:
Selective Call/Call Alert Encode/Decode
- LTR Trunking Signaling Features:
MDC 1200 Signaling
PTT-ID Encode
PTT-ID Decode
Radio Check Decode

- Selective Radio Inhibit Decode
- Data-Operated Squelch (DOS)
- Pre-Time

The Full Keypad model has all of the same regular features as the Limited Keypad model plus the following:

- Dial Phone Numbers
- Manual Access Repeater
Send DTMF tones to repeater
- User-Editable Phone List
- Speed Dial for Radio Call Encode

Programmable Features: Choose up to 8

- **Menu Mode**
Access to the radio menu and the ability to select a menu option
- **Monitor**
Monitor radio traffic
- **Repeater/Talkaround**
Toggle between using the repeater or transmitting directly to another radio
- **Revert Memory Channel**
Instant access to the home channel/talkgroup
- **Store Memory Channel**
Store current channel/talkgroup to the home channel/talkgroup
- **Home Revert Auto Key**
Keys up the radio and transmits an MDC PTT ID (LTR only)
- **Voice Operated Transmission (VOX)**
Hands-free operation with an audio accessory

- **Keypad Lock/Unlock**
Lock/unlock keypad to prevent unauthorized usage
- **Radio Call**
Initiate Quik-Call II and/or DTMF Call Alert or Selective Call Encode from a call list
- **Scan/Nuisance Channel/Talkgroup Delete**
Initiate or stop a scan and delete a nuisance channel/talkgroup while scanning
- **Edit Scan List**
Add, delete or prioritize channels / talkgroups
- **Phone Mode**
Place and receive telephone calls through the repeater
- **Escalator**
Increase the volume of the alarm tones when a radio call is not answered
- **Squelch**
Toggle squelch level between tight and normal squelch

- **Power Level**
Change transmit power between high and low power
- **Lights**
Switch keypad and display backlights on or off

The Full Keypad model has all of the same programmable features as the Limited Keypad model plus the following:

- **Speed Dial**
- **DTMF (Full-Keypad) Specific Features**
DTMF Last Number Redial in Phone Mode
Auto DTMF Access/De-access Code
Manual Entry of DTMF Access/De-access Code

CP SERIES PORTABLE SPECIFICATIONS

GENERAL SPECIFICATIONS

	CP200 VHF	CP200 UHF	CP200-XLS VHF	CP200-XLS UHF
Frequency	136-162 MHz 146-174 MHz	403-440 MHz 438-470 MHz 465-495 MHz	136-162 MHz 146-174 MHz	403-440 MHz 438-470 MHz 465-495 MHz
Channel Capacity	4 or 16 Channels		128 Channels	
Power Supply	7.5 Volts ± 20%		7.5 Volts ± 20%	
Dimensions with Battery				
2250 mAh Li-Ion	127.5 x 61.50 x 45mm (5.0 x 2.4 x 1.75 inches)		127.5 x 61.50 x 45mm (5.0 x 2.4 x 1.75 inches)	
1600 mAh Slim Li-Ion	127.5 x 61.55 x 42mm (5.0 x 2.4 x 1.65 inches)		127.5 x 61.55 x 42mm (5.0 x 2.4 x 1.65 inches)	
1400 mAh NiMH	127.5 x 61.55 x 43mm (5.0 x 2.4 x 1.69 inches)		127.5 x 61.55 x 43mm (5.0 x 2.4 x 1.69 inches)	
950 mAh NiCd	127.5 x 61.50 x 45mm (5.0 x 2.4 x 1.75 inches)		127.5 x 61.50 x 45mm (5.0 x 2.4 x 1.75 inches)	
Weight with Battery				
2250 mAh Li-Ion	370 g (13.04 oz)		370 g (13.04 oz)	
1600 mAh Slim Li-Ion	374 g (13.19 oz)		374 g (13.19 oz)	
1400 mAh NiMH	444 g (15.66 oz)		444 g (15.66 oz)	
950 mAh NiCd	425 g (14.98 oz)		425 g (14.98 oz)	
Average Battery Life ¹	1W 5W	1W 4W	1W 5W	1W 4W
2250 mAh Li-Ion	17 Hrs 14 Hrs	17 Hrs 14 Hrs	17 Hrs 14 Hrs	17 Hrs 14 Hrs
1600 mAh Slim Li-Ion	14 Hrs 12 Hrs	14 Hrs 12 Hrs	14 Hrs 12 Hrs	14 Hrs 12 Hrs
1400 mAh NiMH	11 Hrs 10 Hrs	11 Hrs 10 Hrs	11 Hrs 10 Hrs	11 Hrs 10 Hrs
950 mAh NiCd	9 Hrs 8 Hrs	9 Hrs 8 Hrs	9 Hrs 8 Hrs	9 Hrs 8 Hrs
FCC Designation	ABZ99FT3039 ABZ99FT3045	ABZ99FT4056 ABZ99FT4057 ABZ99FT4058	ABZ99FT3039 ABZ99FT3045	ABZ99FT4056 ABZ99FT4057 ABZ99FT4058

RECEIVER SPECIFICATIONS

	CP200 VHF	CP200 UHF	CP200-XLS VHF	CP200-XLS UHF
Frequency	12.5 kHz 20/25/30 kHz ²	12.5 kHz 20/25/30 kHz ²	12.5 kHz 20/25/30 kHz ²	12.5 kHz 20/25/30 kHz ²
	136-162 MHz 146-174 MHz	403-440 MHz 438-470 MHz 465-495 MHz	136-162 MHz 146-174 MHz	403-440 MHz 438-470 MHz 465-495 MHz
Sensitivity ² (12dB EIA SINAD)	0.25 µV	0.25 µV	0.25µV	0.25µV
Adjacent Channel Selectivity ²	-65 dB -70 dB	-60 dB -70 dB	-65 dB -70 dB	-60 dB -70 dB
Intermodulation ²	-70 dB -70 dB	-70 dB -70 dB	-70 dB -70 dB	-70 dB -70 dB
Frequency Stability ² (-30° to +60° C)	0.00025%	0.00025%	0.00025%	0.00025%
Spurious Rejection ²	-75 dB	-75 dB	-75 dB	-75 dB
Image and 1/2 I-F Rejection ²	-70 dB	-70 dB	-70 dB	-70 dB
Audio Output ² @ < 5% Distortion	500mW	500mW	500mW	500mW

TRANSMITTER SPECIFICATIONS

	CP200 VHF	CP200 UHF	CP200-XLS VHF	CP200-XLS UHF
RF Output	1W / 5W	1W / 4W	1W / 5W	1W / 4W
Frequency	136-162 MHz 146-174 MHz	403-440 MHz 438-470 MHz 465-495 MHz	136-162 MHz 146-174 MHz	403-440 MHz 438-470 MHz 465-495 MHz
Channel Spacing	12.5/20/25 kHz ²		12.5/20/25 kHz ²	
Frequency Stability (-30° to +60° C)	0.00025%		0.00025%	
Spurs/Harmonics ²	-36 dBm < 1 GHz, -30 dBm > 1 GHz		-36 dBm < 1 GHz, -30 dBm > 1 GHz	
Audio Response ²	+1, -3 dB		+1, -3 dB	
From 6dB/octave Preemphasis, 300 to 3000 Hz				
Audio Distortion ²	< 3%		< 3%	
@ 1000 Hz, 60% Rated Maximum Deviation				
FM Noise ²	-40 dB (12.5 kHz) -45 dB (25 kHz) ³		-40 dB (12.5 kHz) -45 dB (25 kHz) ³	
FCC Modulation	16KOF3E 11KOF3E	16KOF3E 11KOF3E	16KOF3E 11KOF3E	16KOF3E 11KOF3E
20/25/30 kHz ²				
12.5 kHz				

PORTABLE MILITARY STANDARDS 810 C, D, E and F

	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F	
	Method	Procedures	Method	Procedures	Method	Procedures	Method	Procedures
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	I
High Temperature	501.1	I, II	501.2	I, II	501.3	I, II	501.4	I, II
Low Temperature	502.1	I	502.2	I, II	502.3	I, II	501.4	I, II
Temperature Shock	503.1	I	503.2	I	503.3	I	503.4	I
Solar Radiation	505.1	I	505.2	I	505.3	I	505.4	I
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I
Humidity	507.1	II	507.2	II, III	507.3	II, III	507.4	III
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	I
Blowing Dust	510.1	I	510.2	I	510.3	I	510.4	I
Vibration	514.2	VIII, X	514.3	I	514.4	I	514.5	I
Shock	516.3	I, II, V	516.3	I, IV	516.4	I, IV	516.5	I

ENVIRONMENTAL

Operating Temperature	-30° to +60° C
Storage Temperature	-40° to +85° C
ESD	IEC 801-2 KV
Thermal Shock	-40° to +80° C
Humidity	95% RH @ 8 Hour
Water and Dust Intrusion	IP 54
Packing Test	Impact test

Accelerated Life Test

Motorola's Accelerated Life Test (ALT) is a developmental process of rigorous laboratory testing that simulates years of field use. Motorola has a firm commitment to quality and reliability. These radios have been designed, manufactured and tested to achieve high levels of component and workmanship quality. Motorola radios are designed to minimize costly repairs and downtime.

Terrycomm
4155 Dow Rd. Unit N
Melbourne, FL 32934
Tel: 321-253-6067
Fax: 321-253-9529
www.terrycomm.com

¹ 5% receive, 5% transmit, 90% standby.

² All electrical specifications and methods refer to EIA/TIA 603 standards. Specifications shown are typical and subject to change without notice.

³ 25 kHz not available in the US on new equipment after 1/1/2011.